

# Simple Perfection!

Plain and simple, you'll build the perfect seedbed with the Perfecta® field cultivator. Save fuel and time by tilling, leveling and finishing in a single pass. It's ideal for row-crop, orchard, vineyard, track and arena grooming and a multitude of other tillage applications.



- Heavy-duty four-bar frame for added durability
- Three rows of staggered high-clearance S-tines for full-width tillage
- Underframe clearance of 20" for superior residue flow
- Tines spaced 18" side-to-side and 20" front-to-rear for 6"-overall spacing



- S-Tines till from 2" to 6" deep and are available in three models
  - Model 10 features a 1/2" x 1 1/4" S-tine with 2 3/4" goosefoot shovel for effective soil finishing in previously worked soils
  - Model 12 with 1/2" x 1 3/4" S-tines and 4" sweeps which provide effective penetration in heavier, unworked soils and rocky conditions
  - Model 14 features 9/16" x 1 3/4" heavy-duty, edge-bent tines and 7" sweeps for working in the toughest soils for maximum tillage and consistent depth
  - The two outermost tines on all models have points
- The leveling bar, with choice of straight spiked teeth, or round diagonal teeth, knocks down ridges and breaks clods
  - Forged spike teeth provide excellent leveling in low residue
  - Diagonal, round one-bar heat-treated teeth perform best for moderate leveling in higher-residue fields
  - Leveling bar position is tool-free adjustable for varying soil and residue conditions
- Aggressive, Unverferth 12" diameter Rolling Harrow® baskets with serrated, spiraled-edge design complete the tillage operation by knocking soil from weed roots and leaving them on the surface to wilt and die
  - Leaves the finer soil particles beneath the surface for optimum seed-tosoil contact and coarser materials on top to resist crusting and erosion for a near-perfect seedbed
  - Shielded, 3-bolt bearings feature a 1" round bore and triple-lip seals for longer life
  - Reversible baskets for increased firming action
  - Ideal for chemical and residue incorporation
- Gauge wheels are tool-free adjustable
  - 16.5 x 6.5-8 single-ply tires standard on rigid 10' to 15' sizes and all bedded models
  - Single 20.5x8-10 ply tires on folding models with 4', 5' and 6' wings
  - Dual 20.5x8-10 gauge wheels on rigid 18' and 20' units and folding models with 7' and 8' wings
- An optional light package is also available for added transport safety while on roadways





The bedded-crop model of the Perfecta is the ideal implement for finishing beds before planting. While uprooting growing weeds to wilt and die, the Perfecta is also loosening and aerating the soil for optimum seed-tosoil or root-to-soil contact. Models are available for a variety of bed widths.









Perfecta field cultivators from 4' through 10' feature tapered sides for close work without injury to trees, shrubs, bushes or vines when working orchards, groves or vineyards.





The Perfecta field cultivator is lighter, pulls easier, covers more acres and is more versatile than a comparable-sized disk. The horsepower requirement is 4-7 hp per foot. It's available in a variety of configurations, working widths from 4' to 28' and your choice of a durable, high-gloss red or green powder-coat finish.

See your Unverferth dealer today or check our website at umequip.com for complete details on the Perfecta field cultivators.

## Perfecta® Field Cultivators



### Specifications

#### Folding Perfecta Models 10, 12 and 14

Cat. 2 Std. and Quick, Cat. 3 Std. and Quick, Cat. 3 Narrow Quick

#### 12' Base with Folding Wings

Over		Folded	Transport		Number of	Rollers, Width Number			:h	Number of Leveling	Approx. weight
Wid	th Width	Height	Width	Size S-Tines		3'	4'	5'	6'	Bar Teeth	(lbs.)
28	27' 6"	9' 11"	15'	8'	55	l	4	1	2	56	3,710
26	25' 6"	9' 1"	15'	7'	51	2	2	1	2	52	3,525
24	23' 6"	8' 2"	15'	6'	47	l	_	l	4	48	3,105
22	21' 6"	7' 3"	15'	5'	43	_	_	2	2	44	2,925
20	19' 6"	6' 4"	15'	4'	39	_	2	_	2	40	2,740

9' Base with Folding Wings											
Overall	Working	Folded	Transport	Wing Numb Size S-Tir		Rollers, Width Number				Number of Leveling	Approx. Weight
Width	Width	Height	Width		5-Tines	3'	4'	5'	6'	Bar Teeth	(lbs.)
26'	25' 6"	10' 3"	12' 6"	8'	51	_	4	2	_	52	3,585
24'	23' 6"	9' 3"	12' 6"	7'	47	2	2	2	_	48	3,280
22'	21' 6"	8' 2"	12' 6"	6'	41	_		2	2	44	2,860
20'	19' 6"	7' 3"	12' 6"	5'	37	_		4	_	40	2,675
18'	17' 6"	6' 4"	12' 6"	4'	33	_	2	2	_	36	2,495

#### Rigid Perfecta Models 10, 12 and 14

#### 10'-20' Cat. 2 Std. and Quick, Cat. 3 Std. and Quick, Cat. 3 Narrow Quick; 8' and smaller Cat. 1 Std. and Opt. Quick

	Overall	Working	Transport Width	Number of S-Tines	Rolle	rs, Wic	lth Nu	mber	Number of Leveling Bar	Approx. Weight (lbs.)
	Width	Width			3'	4'	5'	6'	Teeth	Approx. Height (ibs.)
ý	20'	19' 6"	20'	39	_	_	4	_	40	2,530
	18'	17' 6"	20'	35	—		_	3	36	2,330
	15'	14' 6"	15'	29	<b>-</b>		3		30	1,870
	14'	13' 6"	15'	27	—	1	2		28	1,710
N	13'	12' 6"	13'	25	—	2	1		26	1,630
	12'	11' 6"	13'	23	—	_	<b>—</b>	2	24	1,500
,	10'	9' 6"	10'	19	_	_	2	_	20	1,280
g	8'	7' 6"	8'	15	—	2		_	16	890
	7'	6' 6"	7'	13	1	1	_	_	14	805
J	6'	5' 6"	6'	11	—		_	1	12	625
4	5'	4' 6"	5'	9	_	_	1	_	10	560
	4'	3' 6"	4'	7	_	1	_	_	8	495

# **Unverferth**® Tillage

### **Specifications**

#### Perfecta for Bedded Crops

10'–28' Cat. 2 Std. and Quick, Cat. 3 Std. and Quick, Cat. 3 Narrow Quick; 7' accepts Cat. 1 Std. and Opt. Quick Hitch (optional adapter pins required)

Bed	Description		S-Tines	S	hovels	Rolling	Approx. Weight (lbs.)
Width	Description	Qty.	Size	Qty.	Size	Baskets	
		6	30" Adj.	6	10"		2,745
66"	28' for 5 - 66" Beds - Folding	20	19.5"	20	2.75"	5 - 4 ft.	
		40	16"	40	1"		
		6	30" Adj.	6	10"		3,365
60"	25' for 5 - 60" Beds - Folding	20	19.5"	20	2.75"	5 - 4 ft.	
		40	16"	40	1"	]	
		4	30" Adj.	4	10"	3 - 6 ft.	2,720
84"	22' for 3 - 84" Beds - Folding	6	19.5"	6	2.75"		
		30	16"	30	1"	1	
		4	30" Adj.	4	10"		
80"	22' for 3 - 80" Beds - Folding	6	19.5"	6	2.75"	3 - 6 ft.	3,300
		30	16"	30	1"	1	
		2	30" Adj.	2	10"	1 - 6 ft.	715
80"	7' for 1 - 80" Bed - Rigid	2	19.5"	2	2.75"		
		9	16"	9	1"		
		4	30" Adj.	4	10"	3 - 5 ft.	
66"	20' for 3 - 66" Beds - Rigid	6	19.5"	6	2.75"		2,240
		24	16"	24	1"		
		4	30" Adj.	4	10"	3 - 4 ft.	1,675
60"	15' for 3 - 60" Beds - Rigid	12	19.5"	12	2.75"		
		24	16"	24	1"		
		5	30" Adj.	5	10"	4 - 2 ft.	1,640
40"	15' for 4 - 40" Beds - Rigid	8	19.5"	8	2.75"		
		20	16"	20	1"		
		5	30" Adj.	5	10"		1,640
39"	15' for 4 - 39" Beds - Rigid	8	19.5"	8	2.75"	4 - 3 ft.	
		20	16"	20	1"		
		5	30" Adj.	5	10"		1,640
38"	15' for 4 - 38" Beds - Rigid	8	19.5"	8	2.75"	4 - 3 ft.	
		20	16"	20	1"		
		5	30" Adj.	5	10"	4 - 3 ft.	1,640
36"	12' for 4 - 36" Beds - Rigid	8	19.5"	8	2.75"		
		20	16"	20	1"		
		7	30" Adj.	7	10"		1,960
30"	15' for 6 - 30" Beds - Rigid	12	19.5"	12	2.75"	3 - 5 ft.	
		24	16"	24	1"		

Due to continuing improvements in the design and manufacture of Unverferth products, all specifications contained herein are subject to change without notice.



P.O. Box 357 • Kalida, Ohio 45853 (419) 532-3121 unverferth.com

1-800-322-6301

Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. Unverferth Manufacturing Co., Inc., supports the efforts of Farm Safety 4 Just Kids and all other organizations that promote farm safety.

©2016 Unverferth Manufacturing Co., Inc. Printed in U.S.A.

® ™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon and Canada



